

### IPX 能量回收装置型号及参数

序号	型号	接口尺寸	流量范围 m <sup>3</sup> /h	额定压力		润滑流量 m <sup>3</sup> /h	压力损失 max		能量回收效率	过流材质	电机功率 kW
				psi	bar		psi	bar			
1	IPX-7	1.5"	1.5~7.0	1200	82.7	0.1~0.3	13	0.9	94.63%	SUS2507	0.55
2	IPX-13	1.5"	7.0~12.7	1200	82.7	0.1~0.3	15	1	96.43%	SUS2507	0.55
3	IPX-16	2"	12.8~15.8	1200	82.7	0.2~0.5	12	0.8	95.87%	SUS2507	0.55
4	IPX-19	2"	15.9~18.9	1200	82.7	0.2~0.5	13	0.9	96.27%	SUS2507	0.55
5	IPX-22	2"	19.0~22.0	1200	82.7	0.2~0.5	15	1	96.52%	SUS2507	0.55
6	IPX-25	2.5"	22.0~25.4	1200	82.7	0.4~0.8	12	0.8	95.88%	SUS2507	0.75
7	IPX-31	2.5"	25.5~31.3	1200	82.7	0.4~0.8	13	0.9	96.36%	SUS2507	1.1
8	IPX-38	2.5"	31.4~37.8	1200	82.7	0.4~0.8	15	1	96.67%	SUS2507	1.1
9	IPX-44	3"	37.9~44.2	1200	82.7	0.6~1.2	12	0.8	96.32%	SUS2507	1.5
10	IPX-50	3"	44.3~50.0	1200	82.7	0.6~1.2	13	0.9	96.51%	SUS2507	1.5
11	IPX-57	3"	50.1~56.4	1200	82.7	0.6~1.2	15	1	96.66%	SUS2507	1.5
12	IPX-66	4"	56.5~66.2	1200	82.7	0.8~1.5	12	0.8	96.77%	SUS2507	2.2
13	IPX-75	4"	63.1~75.0	1200	82.7	0.8~1.5	13	0.9	96.91%	SUS2507	2.2
14	IPX-85	4"	75.1~85.0	1200	82.7	0.8~1.5	13	0.9	97.15%	SUS2507	3.0
15	IPX-95	4"	85.1~95.0	1200	82.7	0.8~1.5	15	1	97.21%	SUS2507	3.0